



Advance Features Include:

- ✓ High Capacity Dual Range: 0 ~ 30 X 0.01 lb / 30 ~ 60 X 0.02 lb
- ✓ POS / PC / Cash Register Interface (Option)
- ✓ Bright Vacuum Fluorescent Displays
- ✓ Percent Tare Feature!
- ✓ 6 Digit Total & Unit Pricing
- ✓ Direct PLU keys: 6 (Standard) or 38 (Pole)
- ✓ PLUs Can Store Tare, Price, & Percent Tare Data!



PC-100 Feature Guide

- ❑ Rugged design for years of maintenance-free operation
- ❑ Heavy gauge Stainless Steel platter
- ❑ Quick-Response Weight display
- ❑ POS / Check-Stand option through RS-232 port
- ❑ Tough high quality UV-sealed keypad
- ❑ Compact medium-sized footprint design
- ❑ Standard PC-Style removable power cord
- ❑ User-friendly PLU programming
- ❑ Quick operation keypad for high throughput
- ❑ Optional RS-232 port & Interface cable
- ❑ Compatible with most PCs and Cash Registers
- ❑ 100 Indirect PLUs



Technical Specifications

Model:	PC-100	
Maximum Capacity:	60 lb <i>Dual Range</i>	
Minimum Graduation:	Dual Range 0 to 30 lb x 0.01 lb / 30 to 60 lb x 0.02 lb	
Maximum Tare:	Full Capacity 0 to 60.00 lb	
Internal Resolution:	60,000 Counts (minimum)	
A/D Conversion Rate:	9 Updates / second	
Direct PLU Keys:	Standard Display: Up to 6 Direct PLUs Pole Display: Up to 38 Direct PLUs	
Indirect PLUs:	100 Indirect PLUs	
Vacuum Fluorescent Displays:	Weight: 5 Digits,	999.99 (60 lb max)
	Unit Price: 6 Digits,	9999.99 max
	Total Price: 6 Digits,	9999.99 max
Platter Size:	Width: 350 mm / 13.8"	
	Length: 270 mm / 10.6"	
Product Dimensions:	Pole Display	Standard Display
	Width: 365 mm / 14.4"	Width: 365 mm / 14.4"
	Length: 365 mm / 14.4"	Length: 365 mm / 14.4"
Power Requirements:	Height: 470 mm / 18.5"	Height: 160 mm / 6.3"
	115 Volts AC @ 60 Hz	

Options

<input type="checkbox"/> RS-232C Interface Board	<input type="checkbox"/> Fish Tray Optional Platter
<input type="checkbox"/> RS-232C Cable for PC or Cash Register	<input type="checkbox"/> Wet-Proof Protective Overlay

ATRON
SYSTEMS INC.
West Caldwell, NJ 07006
www.atronsystems.com

Easy Weigh™

Distributed by:

*NOTE: Specifications are subject to change without notice.